

§ 851.24

determines to be necessary to protect the safety and health of workers.

[71 FR 6931, Feb. 9, 2006, as amended at 80 FR 69566, Nov. 10, 2015]

§ 851.24 Functional areas.

(a) Contractors must have a structured approach to their worker safety and health program which at a minimum, include provisions for the following applicable functional areas in their worker safety and health program: construction safety; fire protection; firearms safety; explosives safety; pressure safety; electrical safety; industrial hygiene; occupational medicine; biological safety; and motor vehicle safety.

(b) In implementing the structured approach required by paragraph (a) of this section, contractors must comply with the applicable standards and provisions in appendix A of this part, entitled "Worker Safety and Health Functional Areas."

§ 851.25 Training and information.

(a) Contractors must develop and implement a worker safety and health training and information program to ensure that all workers exposed or potentially exposed to hazards are provided with the training and information on that hazard in order to perform their duties in a safe and healthful manner.

(b) The contractor must provide:

(1) Training and information for new workers, before or at the time of initial assignment to a job involving exposure to a hazard;

(2) Periodic training as often as necessary to ensure that workers are adequately trained and informed; and

(3) Additional training when safety and health information or a change in workplace conditions indicates that a new or increased hazard exists.

(c) Contractors must provide training and information to workers who have worker safety and health program responsibilities that is necessary for them to carry out those responsibilities.

§ 851.26 Recordkeeping and reporting.

(a) *Recordkeeping.* Contractors must:

(1) Establish and maintain complete and accurate records of all hazard in-

10 CFR Ch. III (1–1–16 Edition)

ventory information, hazard assessments, exposure measurements, and exposure controls.

(2) Ensure that the work-related injuries and illnesses of its workers and subcontractor workers are recorded and reported accurately and consistent with DOE Manual 231.1–1A, Environment, Safety and Health Reporting Manual, September 9, 2004 (incorporated by reference, see § 851.27).

(3) Comply with the applicable occupational injury and illness record-keeping and reporting workplace safety and health standards in § 851.23 at their site, unless otherwise directed in DOE Manual 231.1–1A.

(4) Not conceal nor destroy any information concerning non-compliance or potential noncompliance with the requirements of this part.

(b) *Reporting and investigation.* Contractors must:

(1) Report and investigate accidents, injuries and illness; and

(2) Analyze related data for trends and lessons learned (reference DOE Order 225.1A, Accident Investigations, November 26, 1997).

§ 851.27 Reference sources.

(a) *Materials incorporated by reference—*(1) *General.* The following standards which are not otherwise set forth in part 851 are incorporated by reference and made a part of part 851. The standards listed in this section have been approved for incorporation by reference by the Director of the Federal Register in accordance with 5 U.S.C. 552(a) and 1 CFR part 51.

(2) *Availability of standards.* The standards incorporated by reference are available for inspection at:

(i) National Archives and Records Administration (NARA). For more information on the availability of this material at NARA, call 202-741-6030, or go to: http://www.archives.gov/federal_register/code_of_federal_regulations/ibr_locations.html

(ii) U.S. Department of Energy, Office of Environment, Health, Safety and Security, Forrestal Building, 1000 Independence Ave., SW., Washington, DC 20585.

(iii) American National Standards Institute Headquarters, 25 West 43rd

Department of Energy

§ 851.31

Street, New York, NY 10036. Telephone number: 212-642-4980, or go to: <http://www.ansi.org>.

(iv) National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02169. Telephone: 617 770-3000, or go to: <http://www.nfpa.org>.

(v) American Conference of Governmental Industrial Hygienist (ACGIH), 1330 Kemper Meadow Drive, Cincinnati, OH 45240. Telephone number 513-742-2020, or go to: <http://www.acgih.org>.

(vi) American Society of Mechanical Engineers (ASME), P.O. Box 2300 Fairfield, NJ 07007. Telephone: 800-843-2763, or go to: <http://www.asme.org>.

(b) *List of standards incorporated by reference.* (1) American National Standards Institute (ANSI) Z88.2, "American National Standard for Respiratory Protection," (1992).

(2) ANSI Z136.1, "Safe Use of Lasers," (2000).

(3) ANSI Z49.1, "Safety in Welding, Cutting and Allied Processes," sections 4.3 and E4.3, (1999).

(4) National Fire Protection Association (NFPA) 70, "National Electrical Code," (2005).

(5) NFPA 70E, "Standard for Electrical Safety in the Workplace," (2004).

(6) American Conference of Governmental Industrial Hygienists, "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices," (2005).

(7) American Society of Mechanical Engineers (ASME) Boilers and Pressure Vessel Code, sections I through XII including applicable Code Cases, (2004).

(8) ASME B31 (ASME Code for Pressure Piping) as follows:

(i) B31.1—2001—Power Piping, and B31.1a—2002—Addenda to ASME B31.1—2001;

(ii) B31.2—1968—Fuel Gas Piping;

(iii) B31.3—2002—Process Piping;

(iv) B31.4—2002—Pipeline Transportation Systems for Liquid Hydrocarbons and Other Liquids;

(v) B31.5—2001—Refrigeration Piping and Heat Transfer Components, and B31.5a—2004, Addenda to ASME B31.5—2001;

(vi) B31.8—2003—Gas Transmission and Distribution Piping Systems;

(vii) B31.8S—2001—Managing System Integrity of Gas Pipelines;

(viii) B31.9—1996—Building Services Piping;

(ix) B31.11—2002—Slurry Transportation Piping Systems; and

(x) B31G—1991—Manual for Determining Remaining Strength of Corroded Pipelines.

(9) DOE Manual 231.1-1A, Environment, Safety and Health Reporting Manual, September 9, 2004.

(10) DOE Manual 440.1-1A, DOE Explosives Safety Manual, Contractor Requirements Document (Attachment 2), January 9, 2006.

[71 FR 6931, Feb. 9, 2006, as amended at 71 FR 68733, Nov. 28, 2006; 80 FR 5009, Jan. 30, 2015]

Subpart D—Variances

§ 851.30 Consideration of variances.

(a) Variances shall be granted by the Under Secretary after considering the recommendation of the Associate Under Secretary for Environment, Health, Safety and Security. The authority to grant a variance cannot be delegated.

(b) The application must satisfy the requirements for applications specified in § 851.31.

[71 FR 6931, Feb. 9, 2006, as amended at 71 FR 68733, Nov. 28, 2006; 80 FR 5009, Jan. 30, 2015]

§ 851.31 Variance process.

(a) *Application.* Contractors desiring a variance from a safety and health standard, or portion thereof, may submit a written application containing the information in paragraphs (c) and (d) of this section to the appropriate CSO.

(1) The CSO may forward the application to the Associate Under Secretary for Environment, Health, Safety and Security.

(2) If the CSO does not forward the application to the Associate Under Secretary for Environment, Health, Safety and Security, the CSO must return the application to the contractor with a written statement explaining why the application was not forwarded.

(3) Upon receipt of an application from a CSO, the Associate Under Secretary for Environment, Health, Safety and Security must review the application for a variance and make a written recommendation to: